







22 LITERS MOBILE REFRIGERATED CONTAINERS



32 LITERS MOBILE REFRIGERATED CONTAINERS







22 LITERS – TOP LOADER

Technical designation	T0022 FDN	T0022 FDH
Temperature range	-24 °C  	+40 °C to -24 °C  
Product code	81 0000 00 0484	81 0000 00 0485
Voltage	12 / 24 VDC	12 / 24 VDC
Max. current draw, direct current	9 A at 12 V	9 A at 12 V
Wall foam insulation	65 - 70 mm PU*	65 - 70 mm PU*
Refrigerant	R134a	R134a
Weight	20.5 kg	21 kg
External dimensions (W x D x H)	375 x 585 x 480 mm	375 x 585 x 480 mm

* PU = wall foam insulation with polyurethane rigid foam
Standard model without battery packs. Equipped with one DC input. Container only available on special request.

32 LITERS – TOP LOADER

Technical designation	T0032 FDN	T0032 FDH
Temperature range	-24 °C  	+40 °C to -24 °C  
Product code	81 0000 00 0486	81 0000 00 0487
Voltage	12 / 24 VDC	12 / 24 VDC
Max. current draw, direct current	9 A at 12 V	9 A at 12 V
Wall foam insulation	65 - 70 mm PU*	65 - 70 mm PU*
Refrigerant	R134a	R134a
Weight	22.5 kg	22.5 kg
External dimensions (W x D x H)	390 x 670 x 480 mm	390 x 670 x 480 mm

* PU = wall foam insulation with polyurethane rigid foam
Standard model without battery packs. Equipped with one DC input. Container only available on special request.

