







56 LITERS MOBILE REFRIGERATED CONTAINERS



82 LITERS MOBILE REFRIGERATED CONTAINERS








56 LITERS – TOP LOADER

Technical designation	T0056 FDN	T0056 FDH
Temperature range	-24 °C  	+40 °C to -24 °C  
Product code	81 0000 00 0488	81 0000 00 0489
Voltage	12 / 24 VDC	12 / 24 VDC
Max. current draw, direct current	9 A at 12 V	9 A at 12 V
Wall foam insulation	70 mm PU*	70 mm PU*
Refrigerant	R134a	R134a
Weight	33 kg	33 kg
External dimensions (W x D x H)	495 x 800 x 500 mm	495 x 800 x 500 mm

* PU = wall foam insulation with polyurethane rigid foam
Standard model without battery packs. Equipped with two DC inputs.
Accessories depend on the model.

82 LITERS – TOP LOADER

Technical designation	T0082 FDN	T0082 FDH	T0082 XFDN
Temperature range	-24 °C  	+40 °C to -24 °C  	-35 °C 
Product code	81 0000 00 0490	81 0000 00 0491	81 0000 00 0492
Voltage	12 / 24 VDC	12 / 24 VDC	12 VDC
Max. current draw, direct current	9 A at 12 V	9 A at 12 V	25 A at 12 V
Wall foam insulation	80 mm PU*	80 mm PU*	80 mm PU*
Refrigerant	R134a	R134a	R404a
Weight	35 kg	35 kg	40 kg
External dimensions (W x D x H)	560 x 940 x 551 mm	560 x 940 x 551 mm	560 x 940 x 551 mm

* PU = wall foam insulation with polyurethane rigid foam (K < 0.32 W/(m²K))
Standard model without battery packs. Equipped with two DC inputs.
Accessories depend on the model.

