





Refrigerated container with metal feet:
transportable by pallet jack or forklift

915 LITERS MOBILE REFRIGERATED CONTAINERS



915 LITERS – FRONT LOADER

Technical designation	F0915 NDN	F0915 FDN*	F0915 NDH	F0915 FDH
Temperature range	0 °C 	-21 °C 	+30 °C to 0 ° 	+30 °C to -21 °C 
Product code	81 0000 00 0512	81 0000 00 0514	81 0000 00 0513	81 0000 00 0515
Voltage	12 / 24 VDC	12 VDC	12 / 24 VDC	12 VDC
Max. current draw, direct current	20 A at 12 V	32 A at 12 V	20 A at 12 V	32 A at 12 V
Wall foam insulation	100 mm PU**	100 mm PU**	100 mm PU**	100 mm PU**
Refrigerant	R134a	R404a	R134a	R404a
Weight	166 kg	172 kg	169 kg	175 kg
External dimensions (W x D x H)	1,200 x 1,500 x 1,180 mm	1,200 x 1,500 x 1,180 mm	1,200 x 1,500 x 1,180 mm	1,200 x 1,500 x 1,180 mm

* F0915 FDN cannot be operated with 24 V. It can only be operated with an additional, external converter that is not included in the product package.

** PU = wall foam insulation with polyurethane rigid foam ($K < 0.28 \text{ W/(m}^2\text{K)}$)

Standard model without battery packs. Equipped with two DC inputs.

Accessories depend on the model.

